FRONTEQ



Götene Flex Buckets 700-2500 litres

Flex bucket from Götene with adjustable cutting edge. The bucket is specially designed for rock clearing and uncovering of rock.

The cutting edge is mechanically tiltable by 40 degrees in both directions. The cutting edge follows the ground without hydraulics. The bolt-on edge is bolted and replaceable. Does not require a tilt rotator or hydraulic tilt.

High-strength, top-quality material. S-attachment is standard, available with B20-B27 attachment as an option.

Götene's flex buckets are suitable for crawler excavators between 14 and 50 tonnes.

Characteristics

- Optimal angles for digging and emptying.
- Optional S-coupler included.
- The cutting edge is tiltable 40 degrees to the left and right.
- The bolt-on edge is bolted and replaceable.



Teknisk data

Item no.	Product name	Volume SAE	Weight, approx. (kg)	Width (mm)	Edge system	Recommended machine weight (tonnes)
10240FLEX	Flex bucket	700	670	1060	Bolt-on edge	14-16
10264FLEX	Flex bucket	900	950	920	Bolt-on edge	16-20
10275FLEX	Flex bucket	1200	1200	1200	Bolt-on edge	20-25
80286FLEX	Flex bucket	1475	1550	1200	Bolt-on edge	25-30
80295FLEX	Flex bucket	1825	1800	1440	Bolt-on edge	30-40
80310FLEX	Flex bucket	2500	2700	1680	Bolt-on edge	40-42
80315FLEX	Flex bucket	2500	2900	1680	Bolt-on edge	45-50

Denna PDF är genererad från https://fronteq.se/en. Vi reserverar oss för felskrivningar och faktafel i texter och tabeller. Vi förbehåller oss även rätten att justera modellutbud och specifikationer utan föregående information. Bilder kan visa produkter i alternativt eller extrautrustat utförande. För mer information och aktuella priser, kontakta info@fronteq.se.