FRONTEQ



Götene VA Bucket Nordic

The VA-bucket from Götene's Nordic series. Narrow design but wider than cable buckets, developed especially for water and sewage excavation work.

The V/A bucket is based on the same principle as the cable bucket. Deeply recessed sides for better material release, but with the width of the depth bucket.

The VA buckets in the Nordic series feature a extended cutting edge, and the roof top and back side are in one piece. This is to save on weight and contribute to better fuel economy.

Götene's VA bucket is largely built in Hardox 500 TUF for best durability. S355 is used in the back side.

Suitable for excavators between 7 and 22 tonnes.

Characteristics

- Is built in Hardox 500 TUF while the backside is in S355.
- VA buckets have an extended, set forward cutting edge.
- Extra cut-out sides.
- Optimal angles for best digging and dumping.
- Wear strips are standard on all VA buckets.
- Backside and roof top in one piece.

Note: Buckets in the Götene Nordic series are only available with S-couplers. Specified weights in the product data table may differ depending on the coupler size.

Teknisk data

Art. No.	Product name	Machine weight (tonnes)	Volume SAE	Width (mm)	Recommended machine weight (tonnes)
59210S	V/A bucket Nordic	7 - 10	350	600	260
59212S	V/A bucket Nordic	8 - 12	415	700	284
59215S	V/A bucket Nordic	10 - 14	520	700	381
59218S	V/A bucket Nordic	10 - 14	610	800	415
59219S	V/A bucket Nordic	12 - 16	700	900	450
59220S	V/A bucket Nordic	14 - 18	740	800	532
59225S	V/A bucket Nordic	16 - 20	850	900	575
59230S	V/A bucket Nordic	18 - 22	950	1000	616

Denna PDF är genererad från https://fronteq.se/en. Vi reserverar oss för felskrivningar och faktafel i texter och tabeller. Vi förbehåller oss även rätten att justera modellutbud och specifikationer utan föregående information. Bilder kan visa produkter i alternativt eller extrautrustat utförande. För mer information och aktuella priser, kontakta info@fronteq.se.