FRONTEQ



Götene Intermediate tilt

Intermediate tilt with upright cylinders from Götene. Provides increased flexibility for really large excavators.

The Götene Intermediate tilt is used for larger excavators where increased range of motion is desired, but a tiltrotator is not wanted or cannot be used.

The construction is powerful and robust. The intermediate tilt can be supplied with most attachments and also directly mounted to the machine if desired.

Suitable for crawled excavators between 30 and 50 tonnes.

Characteristics

- Robust construction.
- Robust upright hydraulic cylinders.
- Robusta cylinder protector.
- Can be delivered with the most common quick coupler types. Can also be direct mounted if desired.



Teknisk data

Item no.	Product name	Attachment	Weight, approx. (kg)	Cylinders	Recommended machine weight (tonnes)
17230B20M	Intermediate tilt B20/B20	B 20	800	2 pcs	30
17230S70M	Intermediate tilt S70/S70	S 70	800	2 pcs	30
17230B27M	Intermediate tilt B27/B27	B 27	820	2 pcs	30
17230S80M	Intermediate tilt S80/S80	S 80	1000	2 pcs	30
17250B30M	Intermediate tilt B30/B30	B 30	1280	2 pcs	50
17250S80M	Intermediate tilt S80/S80	S 80	1280	2 pcs	50
17250S90M	Intermediate tilt S90/S90	S 90	1300	2 pcs	50
17250S100M	Intermediate tilt S100/S100	S 100	1320	2 pcs	50

Denna PDF är genererad från https://fronteq.se/en. Vi reserverar oss för felskrivningar och faktafel i texter och tabeller. Vi förbehåller oss även rätten att justera modellutbud och specifikationer utan föregående information. Bilder kan visa produkter i alternativt eller extrautrustat utförande. För mer information och aktuella priser, kontakta info@fronteq.se.